


N-Channel Enhancement Mode Power MOSFET


Features:

- Low On Resistance
- Low Gate Charge
- Fast Switching Characteristic

TO-220FP



BV_{DSS}	100V
$I_D @ V_{GS}=10V, T_C=25^\circ C$	25A
$I_D @ V_{GS}=10V, T_A=25^\circ C$	13A
$R_{DS(ON)}$ typ. @ $V_{GS}=10V, I_D=10A$	8.8m Ω



G : Gate S : Source D : Drain

Ordering Information

Device	Package	Shipping
KE8D5N10RFP	TO-220FP (RoHS compliant)	50 pcs/tube, 20 tubes/box, 5 boxes / carton

Absolute Maximum Ratings (T_A=25°C)

Parameter	Symbol	Limits	Unit
Drain-Source Voltage	V _{DS}	100	V
Gate-Source Voltage	V _{GS}	±20	
Continuous Drain Current @ V _{GS} =10V, T _C =25°C	I _D	25	A
Continuous Drain Current @ V _{GS} =10V, T _C =100°C		16	
Continuous Drain Current @ V _{GS} =10V, T _A =25°C		13	
Continuous Drain Current @ V _{GS} =10V, T _A =70°C		10	
Pulsed Drain Current	I _{DM}	100	
Continuous Body Diode Forward Current @ T _C =25°C	I _S	11	mJ
Avalanche Current @ L=0.1mH	I _{AS}	15	
Avalanche Energy @ L=0.5mH	E _{AS}	36	W
Total Power Dissipation	T _C =25°C	14	
	T _C =100°C	5.6	
	T _A =25°C	3.9	
	T _A =70°C	2.5	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	-55~+150	°C

Thermal Data

Parameter	Symbol	Steady State	Unit
Thermal Resistance, Junction-to-case	R _{θJC}	9	°C/W
Thermal Resistance, Junction-to-ambient	R _{θJA}	32	

Note:

- *a. The power dissipation P_D is based on T_{J(MAX)}=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
- *b. The value of R_{θJA} is measured with the device mounted on 1 in²FR -4 board with 2 oz. copper, in a still air environment with T_A=25°C. The power dissipation P_D is based on R_{θJA} and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
- *c. Repetitive rating, pulse width limited by junction temperature T_{J(MAX)}=150°C. Ratings are based on low frequency and low duty cycles to keep initial T_J=25°C.

Electrical Characteristics (T_A=25°C, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
Static					
BV _{DSS}	100	-	-	V	V _{GS} =0V, I _D =250μA
V _{GS(th)}	2	-	4		V _{DS} =V _{GS} , I _D =250μA
G _{FS}	-	18	-	S	V _{DS} =5V, I _D =10A
I _{GSS}	-	-	±100	nA	V _{GS} =±20V, V _{DS} =0V
I _{DSS}	-	-	1	μA	V _{DS} =80V, V _{GS} =0V
R _{DS(ON)}	-	8.8	11.5	mΩ	V _{GS} =10V, I _D =10A
Dynamic					
C _{iss}	-	1970	-	pF	V _{DS} =50V, V _{GS} =0V, f=1MHz
C _{oss}	-	305	-		
C _{rss}	-	22	-		
R _g	-	0.6	-	Ω	f=1MHz
Q _g *1, 2	-	30	-	nC	V _{DS} =50V, I _D =10A, V _{GS} =10V
Q _{gs} *1, 2	-	9	-		
Q _{gd} *1, 2	-	6.5	-		
t _{d(ON)} *1, 2	-	21	-	ns	V _{DS} =50V, I _D =10A, V _{GS} =10V, R _{GS} =1Ω
t _r *1, 2	-	17	-		
t _{d(OFF)} *1, 2	-	37	-		
t _f *1, 2	-	8.4	-		
Source-Drain Diode					
V _{SD} *1	-	0.8	1.2	V	I _S =10A, V _{GS} =0V
t _{rr}	-	37	-	ns	I _F =10A, dI _F /dt=100A/μs
Q _{rr}	-	48	-	nC	


Note:

*1. Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%


*2. Independent of operating temperature

Typical Characteristics


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Body Diode Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics (Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics



Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature




Typical Characteristics (Cont.)


Single Pulse Power Rating, Junction to Ambient



Transient Thermal Response Curves




TO-220FP Dimension



3-Lead TO-220FP Plastic Package

Marking:



Style: Pin 1.Gate 2.Drain 3.Source

Date Code(counting from left to right) :
 1st code: year code, the last digit of Christian year
 2nd code : month code, Jan→A, Feb→B, Mar→C,
 Apr→D, May→E, Jun→F, Jul→G, Aug→H,
 Sep→J, Oct→K, Nov→L, Dec→M
 3rd and 4th codes : production serial number, 01~99

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.169	0.185	4.35	4.65	e	0.100 TYP		2.54 TYP	
A1	0.051 REF		1.300 REF		F	0.106 REF		2.70 REF	
A2	0.112	0.124	2.85	3.15	Φ	0.138 REF		3.50 REF	
A3	0.102	0.110	2.60	2.80	h	0.000	0.012	0.00	0.30
b	0.020	0.030	0.50	0.75	h1	0.031 REF		0.80 REF	
b1	0.031	0.041	0.80	1.05	h2	0.020 REF		0.50 REF	
b2	0.043	0.053	1.10	1.35	L	1.102	1.118	28.00	28.40
c	0.020	0.030	0.50	0.75	L1	0.043	0.051	1.10	1.30
D	0.392	0.408	9.96	10.36	L2	0.036	0.043	0.92	1.08
E	0.583	0.598	14.80	15.20					