


P-Channel Enhancement Mode MOSFET

Features:


- Low On Resistance
- Low Gate Charge
- Fast Switching Characteristic

TO-252



G D S

BV _{DSS}	-30V
I _D @V _{GS} =-10V, T _C =25°C	-56A
I _D @V _{GS} =-10V, T _A =25°C	-17A
R _{DS(ON)} Typ. @ V _{GS} =-10V, I _D =-15A	4.2mΩ
R _{DS(ON)} Typ. @ V _{GS} =-6V, I _D =-10A	6mΩ



G : Gate S : Source D : Drain

Ordering Information

Device	Package	Shipping
KJD5D0P03	TO-252 (Pb-free lead plating and halogen-free package)	2500 pcs / Tape & Reel

Absolute Maximum Ratings ($T_A=25^\circ C$)

Parameter	Symbol	Limits	Unit
Drain-Source Voltage	V _{DS}	-30	V
Gate-Source Voltage	V _{GS}	± 25	
Continuous Drain Current @ V _{GS} =-10V, T _C =25°C (silicon limit)	I _D	-83	A
Continuous Drain Current @ V _{GS} =-10V, T _C =25°C (package limit)		-56	
Continuous Drain Current @ V _{GS} =-10V, T _C =100°C		-53	
Continuous Drain Current @ V _{GS} =-10V, T _A =25°C		-17	
Continuous Drain Current @ V _{GS} =-10V, T _A =70°C		-14	
Pulsed Drain Current	I _{DM}	-224	
Continuous Body Diode Forward Current @ T _C =25°C	I _S	-56	
Avalanche Current @ L=0.1mH	I _{AS}	-50	
Avalanche Energy @ L=0.5mH	E _{AS}	156	mJ
Total Power Dissipation	T _C =25°C	*a	W
	T _C =100°C	*a	
	T _A =25°C	*b	
	T _A =70°C	*b	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	-55~+150	°C

Thermal Data

Parameter	Symbol	Steady State	Unit
Thermal Resistance, Junction-to-case	R _{θJC}	1.8	°C/W
Thermal Resistance, Junction-to-ambient	R _{θJA}	42	

Note:

- *a. The power dissipation P_D is based on T_{J(MAX)}=150°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
- *b. The value of R_{θJA} is measured with the device mounted on 1 in² FR -4 board with 2 oz. copper, in a still air environment with T_A=25°C. The power dissipation P_D is based on R_{θJA} and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.
- *c. Repetitive rating, pulse width limited by junction temperature T_{J(MAX)}=150°C. Ratings are based on low frequency and low duty cycles to keep initial T_J=25°C.

Electrical Characteristics ($T_A=25^\circ C$, unless otherwise specified)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions	
Static						
BV _{DSS}	-30	-	-	V	V _{GS} =0V, I _D =-250μA	
V _{GS(th)}	-1.5	-	-3		V _{DS} =V _{GS} , I _D =-250μA	
G _{FS}	-	42	-	S	V _{DS} =-5V, I _D =-20A	
I _{GSS}	-	-	±100	nA	V _{GS} =±25V, V _{DS} =0V	
I _{DSS}	-	-	-1	μA	V _{DS} =-24V, V _{GS} =0V	
R _{DSS(ON)}	-	4.2	5.5	mΩ	V _{GS} =-10V, I _D =-15A	
	-	6	12		V _{GS} =-6V, I _D =-10A	
Dynamic						
C _{iss}	-	5300	-	pF	V _{DS} =-15V, V _{GS} =0V, f=1MHz	
C _{oss}	-	900	-			
C _{rss}	-	450	-	nC	V _{DS} =-15V, I _D =-15A, V _{GS} =-10V	
R _g	-	3	-			
Q _g *1, 2	-	86	-	ns	V _{DS} =-15V, I _D =-15A, V _{GS} =-10V	
Q _{gs} *1, 2	-	21	-			
Q _{gd} *1, 2	-	20	-	ns	V _{DS} =-15V, I _D =-15A, V _{GS} =-10V, R _{GS} =1Ω	
t _{d(ON)} *1, 2	-	28	-			
t _r *1, 2	-	24	-	ns	V _{DS} =-15V, I _D =-15A, V _{GS} =-10V, R _{GS} =1Ω	
t _{d(OFF)} *1, 2	-	84	-			
t _f *1, 2	-	27	-			
Source-Drain Diode						
V _{SD} *1	-	-0.8	-1.2	V	I _s =-15A, V _{GS} =0V	
tr	-	28	-	ns	I _F =-15A, dI _F /dt=100A/μs	
Q _{rr}	-	20	-			


Note:

*1. Pulse Test : Pulse Width ≤300μs, Duty Cycle≤2%


*2. Independent of operating temperature

Typical Characteristics


Typical Output Characteristics




Breakdown Voltage vs Ambient Temperature




Static Drain-Source On-State resistance vs Drain Current




Body Diode Current vs Source-Drain Voltage



Static Drain-Source On-State Resistance vs Gate-Source Voltage




Drain-Source On-State Resistance vs Junction Temperature




Typical Characteristics (Cont.)


Capacitance vs Drain-to-Source Voltage




Threshold Voltage vs Junction Temperature




Forward Transfer Admittance vs Drain Current




Gate Charge Characteristics






Maximum Safe Operating Area




Maximum Drain Current vs Junction Temperature




Typical Characteristics (Cont.)




Recommended soldering footprint




Reel Dimension



Carrier Tape Dimension



TO-252 Dimension (C forming)



3-Lead TO-252 Plastic Surface Mount Package

Style: Pin 1.Gate 2.Drain 3.Source
 4.Drain

Date Code(counting from left to right) :
 1st code: year code, the last digit of Christian year
 2nd code : month code, Jan→A, Feb→B, Mar→C, Apr→D
 May→E, Jun→F, Jul→G, Aug→H, Sep→J,
 Oct→K, Nov→L, Dec→M
 3rd and 4th codes : production serial number, 01~99

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.087	0.094	2.200	2.400	L	0.382	0.406	9.712	10.312
A1	0.000	0.005	0.000	0.127	L1	0.114	REF	2.900	REF
b	0.025	0.030	0.635	0.770	L2	0.055	0.067	1.400	1.700
c	0.018	0.023	0.460	0.580	L3	0.063	REF	1.600	REF
D	0.256	0.264	6.500	6.700	L4	0.024	0.039	0.600	1.000
D1	0.201	0.215	5.100	5.460	Φ	0.043	0.051	1.100	1.300
D2	0.190	REF	4.830	REF	θ	0°	8°	0°	8°
E	0.236	0.244	6.000	6.200	h	0.000	0.012	0.000	0.300
e	0.086	0.094	2.186	2.386	V	0.207	REF	5.250	REF