


SCHOTTKY BARRIER RECTIFIER

Features:

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Metal silicon junction ,majority carrier conduction
- Guard ring for overvoltage protection
- Low power loss ,high efficiency
- High current capability ,Low forward voltage drop
- High surge capability
- For use in low voltage ,high frequency inverters, free wheeling ,and polarity protection applications
- Dual rectifier construction
- High temperature soldering guaranteed:260° C/10 seconds,, 0.25"(6.35mm)from case
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC

Mechanical Data:

- Case:** JEDEC ITO-220AB molded plastic body
- Terminals:** Lead solderable per MIL-STD-750,method 2026
- Polarity:** As marked
- Mounting Position:** Any
- Weight:** 0.08ounce, 2.24 gram



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Ratings at 25°C ambient temperature unless otherwise specified ,single phase ,half wave ,resistive or inductive load. For capacitive load, derate by 20%.)

	Symbols	KSRF 2020CT	KSRF 2030CT	KSRF 2045CT	KSRF 2050CT	KSRF 2060CT	KSRF 2080CT	KSRF 20100CT	KSRF 20150CT	KSRF 20200CT	Units						
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	45	50	60	80	100	150	200	Volts						
Maximum RMS voltage	V _{RMS}	14	21	31.5	35	42	56	70	105	140	Volts						
Maximum DC blocking voltage	V _{DC}	20	30	45	50	60	80	100	150	200	Volts						
Maximum average forward rectified current (see Fig.1)	I _(AV)	10.0 20.0								Amps							
Total device										Amps							
Peakforward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I _{FSM}	200.0								Amps							
Maximum instantaneous forward voltage at 20.0 A	V _F	0.60		0.75		0.85		0.88		Volts							
Maximum instantaneous reverse current at rated DC blocking voltage (Note 1)	I _R	0.05		0.005						mA							
T _c =25°C				3.0		5.0											
T _c =125°C																	
Typical thermal resistance (Note 2)	R _{θJC}	4.0								°C/W							
Operating junction temperature range	T _J	-65 to +175								°C							
Storage temperature range	T _{STG}	-65 to +175								°C							

Notes: 1.Pulse test: 300 μs pulse width, 1% duty cycle

2.Thermal resistance from junction to case

FIG.1-FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.6-TYPICAL TRANSIENT THERMAL IMPEDANCE

