

3.0 AMP LOW VF SCHOTTKY BARRIER RECTIFIERS


Features:

- * Low forward voltage drop
- * High current capability
- * High reliability
- * High surge current capability
- * Epitaxial construction

Mechanical Data:

- * Case: Molded plastic
- * Epoxy: UL 94V-0 rate flame retardant
- * Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- * Polarity: Color band denotes cathode end
- * Mounting position: Any
- * Weight: 0.093 grams
- * Both normal and Pb free product are available:
- * Normal: 80~95%Sn, 5~20%Pb
- * Pb free: 99 Sn above can meet Rohs environment substance directive request

DO-214AC



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating 25°C ambient temperature unless otherwise specified.
 Single phase half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

TYPE NUMBER	KS32L	KS34L	UNITS
Marking Code	SS32L	SS34L	
Maximum Recurrent Peak Reverse Voltage	20	40	V
Maximum RMS Voltage	14	28	V
Maximum DC Blocking Voltage	20	40	V
Maximum Average Forward Rectified Current	3.0		A
See Fig. 1			
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	135		A
Maximum Instantaneous Forward Voltage at 3.0A	0.36	0.45	V
Maximum DC Reverse Current Ta=25°C	0.2		mA
at Rated DC Blocking Voltage Ta=100°C	20		mA
Typical Junction Capacitance (Note1)	250		pF
Typical Thermal Resistance R JA (Note 2)	10		°C/W
Operating Temperature Range Tj	-65 — +150		°C
Storage Temperature Range TSTG	-65 — +150		°C

NOTES:

1. Measured at 1MHz and applied reverse voltage of 4.0V D.
2. Thermal Resistance Junction to Ambient

RATING AND CHARACTERISTIC CURVES (KS32L THRU KS34L)

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-TYPICAL FORWARD CHARACTERISTICS




FIG.3-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.4-TYPICAL JUNCTION CAPACITANCE




FIG.5 - TYPICAL REVERSE CHARACTERISTICS

