

## SMB Plastic-Encapsulate Diodes

### Schottky Rectifier Diodes

#### Features:

- $I_{F(AV)}$  8A
- $V_{RRM}$  20V-200V
- High surge current capability
- Polarity: Color band denotes cathode

#### Applications:

- Rectifier

#### Marking

- SS8X

X : From 2 To 20

SMB



#### Limiting Values (Absolute Maximum Rating)

| Item                                 | Symbol      | Unit             | Test Conditions                                          | SS8        |    |    |    |    |    |     |     |     |  |  |  |  |  |  |
|--------------------------------------|-------------|------------------|----------------------------------------------------------|------------|----|----|----|----|----|-----|-----|-----|--|--|--|--|--|--|
|                                      |             |                  |                                                          | 2          | 3  | 4  | 5  | 6  | 8  | 10  | 15  | 20  |  |  |  |  |  |  |
| Repetitive Peak Reverse Voltage      | $V_{RRM}$   | V                |                                                          | 20         | 30 | 40 | 50 | 60 | 80 | 100 | 150 | 200 |  |  |  |  |  |  |
| Maximum RMS Voltage                  | $V_{RMS}$   | V                |                                                          | 14         | 21 | 28 | 35 | 42 | 56 | 70  | 105 | 140 |  |  |  |  |  |  |
| Average Forward Current              | $I_{F(AV)}$ | A                | 60HZ Half-sine wave, Resistance load, TL(Fig.1)          | 8.0        |    |    |    |    |    |     |     |     |  |  |  |  |  |  |
| Surge(Non-repetitive)Forward Current | $I_{FSM}$   | A                | 60Hz Half-sine wave , 1 cycle , $T_a = 25^\circ\text{C}$ | 200        |    |    |    |    |    |     |     |     |  |  |  |  |  |  |
| Junction Temperature                 | $T_J$       | $^\circ\text{C}$ |                                                          | -50~+150   |    |    |    |    |    |     |     |     |  |  |  |  |  |  |
| Storage Temperature                  | $T_{STG}$   | $^\circ\text{C}$ |                                                          | -50 ~ +150 |    |    |    |    |    |     |     |     |  |  |  |  |  |  |

#### Electrical Characteristics ( $T=25^\circ\text{C}$ Unless otherwise specified)

| Item                        | Symbol           | Unit                      | Test Condition                | SS8                       |                   |      |   |      |   |      |    |    |  |  |  |  |  |  |
|-----------------------------|------------------|---------------------------|-------------------------------|---------------------------|-------------------|------|---|------|---|------|----|----|--|--|--|--|--|--|
|                             |                  |                           |                               | 2                         | 3                 | 4    | 5 | 6    | 8 | 10   | 15 | 20 |  |  |  |  |  |  |
| Peak Forward Voltage        | $V_F$            | V                         | $I_F = 8.0\text{A}$           | 0.50                      |                   | 0.65 |   | 0.80 |   | 0.90 |    |    |  |  |  |  |  |  |
| Peak Reverse Current        | $I_{RRM1}$       | mA                        | $V_{RM} = V_{RRM}$            | $T_a = 25^\circ\text{C}$  |                   | 0.1  |   |      |   |      |    |    |  |  |  |  |  |  |
|                             | $I_{RRM2}$       |                           |                               | $T_a = 105^\circ\text{C}$ |                   | 1.0  |   |      |   |      |    |    |  |  |  |  |  |  |
| Thermal Resistance(Typical) | $R_{\theta J-A}$ | $^\circ\text{C}/\text{W}$ | Between junction and ambient  |                           | 112 <sup>1)</sup> |      |   |      |   |      |    |    |  |  |  |  |  |  |
|                             | $R_{\theta J-L}$ |                           | Between junction and terminal |                           | 12 <sup>1)</sup>  |      |   |      |   |      |    |    |  |  |  |  |  |  |

#### Notes:

- <sup>1)</sup> Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.6" x 0.6" (16 mm x 16 mm) copper pad areas

**Typical Characteristics**

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: MAXIMUM NON-REPETITIVE FORWARD URGE CURRENT




FIG.3: TYPICAL FORWARD CHARACTERISTICS






FIG.4: TYPICAL REVERSE CHARACTERISTICS




### SMB Package Outline Dimensions



Dimensions in inches and (millimeters)


### SMB Suggested Pad Layout



**Note:**

1. Controlling dimension: in millimeters.
2. General tolerance:  $\pm 0.05 \text{ mm}$ .
3. The pad layout is for reference purposes only.

**Reel Taping Specifications For Surface Mount Devices- SMB**



**FIG: CONFIGURATION OF SURFACE MOUNTED DEVICES TAPING**

| ITEM                   | SYMBOL | SMBG mm(inch)          |
|------------------------|--------|------------------------|
| Carrier width          | A      | 4.09±0.1(0.161±0.004)  |
| Carrier length         | B      | 5.82±0.1(0.229±0.004)  |
| Carrier depth          | C      | 2.50±0.1(0.100±0.004)  |
| Sprocket hole          | d      | 1.55±0.05(0.061±0.002) |
| Reel outside diameter  | D      | 330±2.0(13±0.079)      |
| Reel inner diameter    | D1     | 75 ±1.0 ( 2.95 ±0.039) |
| Feed hole diameter     | D2     | 13±0.5(0.512±0.020)    |
| Strocket hole position | E      | 1.75±0.1(0.069±0.004)  |
| Punch hole position    | F      | 5.65±0.05(0.222±0.002) |
| Punch hole pitch       | P      | 8.0±0.1(0.315±0.004)   |
| Sprocket hole pitch    | P0     | 4.0±0.1(0.157±0.004)   |
| Embossment center      | P1     | 2.0±0.1(0.079±0.004)   |
| Total tape thickness   | T      | 0.32±0.1(0.013±0.004)  |
| Tape width             | W      | 12.0±0.2(0.472±0.008)  |
| Reel width             | W1     | 16.8±2.0(0.661±0.079)  |

NOTE: Devices are packed in accordance with EIA standard RS-481-A and specification given above.