

SOT-323 Plastic-Encapsulate Transistors

TRANSISTOR (NPN)

SOT- 323

FEATURE


Low Saturation Voltage

MARKING:619

1.BASE

2.EMITTER

3.COLLECTOR



MAXIMUM RATINGS ($T_a=25^{\circ}\text{C}$ unless otherwise noted)









Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage	50	V
V_{CEO}	Collector-Emitter Voltage	50	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current -Continuous	2	A
P_C	Power Dissipation	0.35	W
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient	357	$^{\circ}\text{C}/\text{W}$
P_{CM}	Maximum Power Dissipation (note 1)	0.625	W
$R_{\theta JA}$	Thermal Resistance from Junction to Ambient (note 1)	200	$^{\circ}\text{C}/\text{W}$
T_J, T_{stg}	Operation Junction and Storage Temperature Range	-55~+150	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}\text{C}$ unless otherwise specified)




Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C=100\mu\text{A}, I_E=0$	50			V
Collector-emitter breakdown voltage (note 2)	$V_{(BR)CEO}$	$I_C=10\text{mA}, I_B=0$	50			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E=100\mu\text{A}, I_C=0$	5			V
Collector cut-off current	I_{CBO}	$V_{CB}=40\text{V}, I_E=0$			100	nA
Emitter cut-off current	I_{EBO}	$V_{EB}=4\text{V}, I_C=0$			100	nA
DC current gain (note 2)	$h_{FE(1)}$	$V_{CE}=2\text{V}, I_C=10\text{mA}$	200			
	$h_{FE(2)}$	$V_{CE}=2\text{V}, I_C=0.2\text{A}$	300			
	$h_{FE(3)}$	$V_{CE}=2\text{V}, I_C=1\text{A}$	200			
	$h_{FE(4)}$	$V_{CE}=2\text{V}, I_C=2\text{A}$	100			
	$h_{FE(5)}$	$V_{CE}=2\text{V}, I_C=6\text{A}$		40		
Collector-emitter saturation voltage (note 2)	$V_{CE(sat)1}$	$I_C=0.1\text{A}, I_B=10\text{mA}$			20	mV
	$V_{CE(sat)2}$	$I_C=1\text{A}, I_B=10\text{mA}$			200	mV
	$V_{CE(sat)3}$	$I_C=2\text{A}, I_B=100\text{mA}$			220	mV
Base-emitter saturation voltage (note 2)	$V_{BE(sat)}$	$I_C=2\text{A}, I_B=50\text{mA}$			1	V
Base-emitter on voltage (note 2)	$V_{BE(on)}$	$I_C=2\text{A}, V_{CE}=2\text{V}$			1	V
Output capacitance	C_{ob}	$V_{CB}=10\text{V}, f=1\text{MHz}$			20	pF
Turn-on time	$t_{(on)}$	$V_{CC}=10\text{V}, I_C=1\text{A}, I_{B1}=-I_{B2}=10\text{mA}$		170		ns
Turn-off time	$t_{(off)}$			750		ns
Transition frequency	f_T	$V_{CE}=10\text{V}, I_C=50\text{mA}, f=100\text{MHz}$	100			MHz

Notes :

- Maximum power dissipation is calculated assuming that the device is mounted on a ceramic substrate measuring 15x15x0.6mm.
- Pulse test: Pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2.0\%$.




SOT-323 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

SOT-323 Suggested Pad Layout




Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

SOT-323 Tape and Reel

SOT-323 Embossed Carrier Tape




Packaging Description:


SOT-323 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-323	2.25	2.55	1.19	Ø1.55	1.75	3.50	4.00	4.00	2.00	8.00

SOT-323 Tape Leader and Trailer



SOT-323 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	